



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : D21F 3/02	A1	(11) International Publication Number: WO 99/16967 (43) International Publication Date: 8 April 1999 (08.04.99)
(21) International Application Number: PCT/SE98/01758 (22) International Filing Date: 30 September 1998 (30.09.98) (30) Priority Data: 9703570-3 30 September 1997 (30.09.97) SE (71) Applicant: VALMET-KARLSTAD AB [SE/SE]; P.O. Box 1014, S-651 15 Karlstad (SE). (72) Inventors: PALMGREN, Joakim; Ulvsbygatan 3 A, S-654 64 Karlstad (SE). NYMAN, Mikael; S:a Lagerlöfsgatan 7, S-667 33 Forshaga (SE). BROX, Erik; Trollstigen 20, S-667 33 Forshaga (SE). (74) Agent: ROSTOVANYI, Peter; Awapatent AB, P.O. Box 5117, S-200 71 Malmö (SE).		(81) Designated States: BR, CA, CN, JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <i>In English translation (filed in Swedish).</i>
(54) Title: SHOE PRESS AND METHOD FOR SUPPORTING A PRESS SHOE IN A SHOE PRESS <div data-bbox="451 1138 1123 1600" data-label="Image"> </div> (57) Abstract <p>A method of supporting a press shoe in a shoe press for a paper of board machine, said press shoe (2) forming together with a counter roll (12) an extended nip (N) for a paper or cardboard web (W) and for a flexible circulated belt (12). On the outside of the loading cylinder (3, 4) of the press shoe there is arranged a compartment (15), to which hydraulic fluid is supplied in such a manner that the hydraulic fluid in the compartment directly or indirectly exerts a force upon the press shoe in the direction opposite to that of the force exerted upon the press shoe by the loading cylinder. The cylinder part (4) of the loading cylinder is movably arranged on the piston part (3). Said forces are dimensioned such that in operation they create a gap (16) between the press shoe and the loading cylinder, or between the supporting beam (9) of the press shoe and the loading cylinder, thereby allowing hydraulic fluid to flow out of the compartment (15). In an embodiment of a shoe press as described above, the working chamber (5) of the loading cylinder (3, 4) can communicate with the compartment (15) via a throttle (14). Alternatively, the working chamber and the compartment can be supplied with hydraulic fluid independently of each other.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SHOE PRESS AND METHOD FOR SUPPORTING A PRESS SHOE IN A
SHOE PRESS

The invention relates on the one hand to a method of supporting a press shoe in a shoe press and, on the other hand, to a shoe press.

The invention concerns a shoe press for a paper or
5 board machine, said shoe press having a press shoe which
together with a counter roll forms an extended nip for
a paper or cardboard web and for a flexible circulated
belt, and at least one piston-and-cylinder assembly,
which is arranged between a supporting beam associated
10 with the frame system of the shoe press and the press
shoe and in which hydraulic fluid is supplied to a work-
ing chamber, said working chamber communicating with a
compartment via a throttle, said compartment being ar-
ranged on the outside of the piston-and-cylinder assembly
15 in such a manner that the hydraulic fluid therein exerts
directly or indirectly a force upon the press shoe in the
direction opposite to that of the force exerted upon the
press shoe by the hydraulic fluid in said working cham-
ber.

20 A shoe press as described above is disclosed in
DE-C1-195 15 832, the piston in the piston-and-cylinder
assembly having said compartment.

This prior-art shoe press suffers from the drawback
that lateral forces which in operation affect the press
25 shoe are transmitted to the cylinder jacket and the pis-
ton, which may cause a jam between the press shoe and the
piston.

The object of the invention is to eliminate this
drawback.

30 According to one aspect of the invention, the
drawback implying that lateral forces which in opera-
tion affect a press shoe are transmitted to the cylinder
jacket and the piston has been eliminated by a new method

of supporting the press shoe, said method having the characteristic features as defined in claim 1. Advantageous embodiments are stated in the subclaims.

Moreover, the object has been achieved by means of
5 a shoe press having the characteristic features as defined in claim 4. Preferred embodiments are stated in the subclaims.

Three embodiments of the invention will now be described in more detail with reference to the accompanying drawings, in which
10

Fig. 1 is a cross-sectional view of a first embodiment of the shoe press according to the invention,

Fig. 2 is a cross-sectional view of a second embodiment of the shoe press according to the invention, and

15 Fig. 3 is a cross-sectional view of a third embodiment of the shoe press according to the invention.

The cross-sectional views are taken transversely of the machine direction of the paper machine, and it is understood in this specification and in the claims that
20 the press shoe is a single piece while there is at least one, preferably more piston-and-cylinder assemblies and several compartments distributed in the longitudinal direction of the press shoe (cross-direction of the paper machine).

25 In Figs 1 and 2, reference numeral 1 designates two embodiments of a shoe press and reference numerals 2, 3, 4 designate a press shoe, a piston and a cylinder, respectively. The cylinder 4 and the piston 3 which is movably arranged therein define a chamber 5, to which a
30 hydraulic fluid, e.g. oil, is supplied from a duct 6 in the piston 3 via one or more bores 7 in the piston 3. A radial seal 8 is arranged for the sealing of the chamber 5. The piston 3 is slightly tiltable in the cylinder 4.

Reference numeral 9 designates a horizontal supporting beam located in the shoe press and fixed to the
35 frame. In the embodiment according to Fig. 1, the piston 3 is fixedly connected to the press shoe 2, and the end

wall of the cylinder 4 rests freely on the beam 9, while in the embodiment according to Fig. 2, the piston 3 is fixedly connected to the beam 9 and the press shoe 2 rests freely on the end wall of the cylinder 4. For said
5 connection, use is made of bolts 10. The flexible press belt of the shoe press is designated 11, and the counter roll of the shoe press is designated 12.

In operation with the working chamber 5 pressurized, a paper web W and the circulated press belt 11 guided by
10 the shoe press 1 pass through the nip N between the press shoe 2 and the counter roll 12, the felt F receiving water from the paper web W.

In the end wall of the cylinder 4 there is arranged a through throttle 14 which opens into a shallow compartment or pressure chamber 15 in the end wall of the cylinder 4. Hydraulic fluid in the chamber 5 may thus escape
15 to this compartment via the throttle 14. The area of the compartment 15 is somewhat larger than the inner area of the cylinder 4, which causes the lifting force exerted upon the press shoe 2 by the hydraulic fluid in the compartment 15 at an initial stage of the operation to be
20 greater than the force exerted upon the press shoe 2 by the hydraulic fluid in the working chamber 5. This results in the forming of a gap 16 between the annular bottom surface 4' of the cylinder 4 and the beam 9
25 (Fig. 1) and between the annular top surface 4' of the cylinder 4 and the press shoe 2 (Fig. 2), respectively, through which gap 16 hydraulic fluid constantly flows out of the compartment 15, such that the press shoe 2 floats
30 freely. In operation, there is thus a supporting and lubricating hydraulic fluid film in the gap 16, which can be said to define a hydrostatic bearing between the upper side of the beam 9 and the annular surface 4' in Fig. 1 and between the underside of the press shoe 2 and the
35 annular surface 4' in Fig. 2. A person skilled in the art will, without inventive effort, adapt the diameter of the

throttle 14 and the area of the compartment 15 to each other, thereby obtaining a suitable film thickness.

Fig. 3 illustrates a shoe press having a press shoe 300, a counter roll 312, a circulated press belt 311, a piston-and-cylinder assembly 310 with piston 330 and cylinder 340, and a beam 309 which is fixed to the frame. The piston 330 is attached to the beam 309 by means of bolts 350. The top face of the movable cylinder 340 adjoins the press shoe 300, and in this top face there is a compartment or hydraulic fluid chamber 301, which is defined by an annular flange with an annular surface 340' on the top of the cylinder 340. The compartment 301 is supplied with hydraulic fluid via a sectional pipe 303 which is attached to the longitudinal side edge 304 of the press shoe 300 and which has an inner duct 306, via a bore 302 formed in the press shoe 300 and having bore portions 302' and 302" which are perpendicular to each other, and an opening 308 which is formed in the sectional pipe 303 and constitutes a throttle. For the attachment of the sectional pipe 303 use is made of screws 305 and threaded bores 305' in the press shoe. The working chamber 325 of the piston-and-cylinder assembly 310 is supplied with hydraulic fluid, like in the embodiments above, via a duct system 326, 327 in the piston 330. The difference over the embodiments above thus is that there is no connection between the compartment 301 and the working chamber 325, but the compartment 301 and the working chamber 325 are separately supplied with hydraulic fluid via the ducts 326 and 327 in the piston 330. This arrangement makes it possible to form a gap 336 between the underside of the press shoe 300 and the annular top face 340' of the cylinder 340, through which gap hydraulic fluid can flow out of the compartment 301 while forming a hydrostatic bearing, even if, as illustrated, the surface area of the compartment 301 is smaller than the inner area of the cylinder 340. An O-ring seal

between the cylinder 340 and the piston 330 is designated 380.

It will be appreciated that the object of the invention has thus been achieved, and moreover that the sealing of the above-mentioned prior-art press piston against the press shoe is unnecessary in the inventive shoe press.

The inventive shoe press is applicable also to calendering operations in a paper or board machine.

CLAIMS

1. A method of supporting a press shoe in a shoe
5 press for a paper or board machine, said press shoe (2;
300) forming together with a counter roll (12; 312) an
extended nip (N) for a paper or cardboard web (W) and for
a flexible circulated belt (12; 311), and at least one
10 piston-and-cylinder assembly (3; 4; 330, 340), which is
arranged between a supporting beam (9; 309) associated
with the frame system of the shoe press and the shoe
press and in which hydraulic fluid is supplied to a
working chamber (5; 325), a compartment (15; 301) to
15 which hydraulic fluid is also supplied being arranged on
the outside of the piston-and-cylinder assembly in such
a manner that the hydraulic fluid therein exerts directly
or indirectly a force upon the press shoe in the direc-
tion opposite to that of the force exerted upon the press
shoe by the hydraulic fluid in said working chamber,
20 c h a r a c t e r i z e d in that the cylinder (4; 340) in
the piston-and-cylinder assembly is movably arranged on
the piston (3; 330) of the piston-and-cylinder assembly,
and that said forces are dimensioned such that in opera-
tion they create a gap (16; 336) between the press shoe
25 and the piston-and-cylinder assembly, or between the sup-
porting beam and the piston-and-cylinder assembly, there-
by allowing hydraulic fluid to flow out of the compart-
ment (15; 301).

2. A method as claimed in claim 1, c h a r a c -
30 t e r i z e d in that hydraulic fluid is supplied to the
compartment (15; 301) via a connection (14) between the
working chamber (5; 325) and the compartment.

3. A method as claimed in claim 1, c h a r a c -
t e r i z e d in that the compartment (15; 301) and the
35 working chamber (5; 325) are supplied with hydraulic
fluid independently of each other.

4. A shoe press for a paper machine, said shoe press having a press shoe (2) which together with a counter roll (13) forms an extended nip (N) for a paper or board web and for a flexible circulated belt (12), and which
5 press shoe is pressed against the counter roll (13) by means of at least one piston-and-cylinder assembly (3, 4), which is arranged between a horizontal supporting beam (9) associated with the frame system of the shoe press and the press shoe (2) and in which hydraulic fluid
10 is supplied to a working chamber (5), the working chamber (5) communicating with a compartment (15) via a throttle (14), said compartment (15) being arranged on the outside of the piston-and-cylinder assembly (3, 4) in such a manner that the hydraulic fluid therein exerts directly or
15 indirectly upon the press shoe (2) a force which is opposed to the force exerted upon the press shoe (2) by the hydraulic fluid in said working chamber (5), characterized in that the working chamber (5), the compartment (15) and the throttle (14) are so designed and dimensioned as to create a hydrostatic bearing
20 between the piston-and-cylinder assembly and the press shoe.

5. A shoe press as claimed in claim 4, characterized in that the compartment (15) is arranged
25 in the cylinder (4) of the piston-and-cylinder assembly.



6. A shoe press as claimed in claim 4 or 5, characterized in that the compartment (15) is open towards the press shoe (2), the piston (3) of the
30 piston-and-cylinder assembly being fixedly connected to the supporting beam (9).

7. A shoe press as claimed in claim 4 or 5, characterized in that the compartment (15) is open towards the supporting beam (9), the piston (3) of
35 the piston-and-cylinder assembly being fixedly connected to the press shoe (2).

8. A shoe press as claimed in any one of claims 4-7, characterized in that the area of the compartment (15) is larger than the area of the working chamber (5).

5 9. A shoe press for a paper machine, said shoe press having a press shoe (300) which together with a counter roll (312) forms an extended nip (N) for a paper or cardboard web (W) and for a circulated flexible belt (311), and which is pressed against the counter roll (312) by
10 means of at least one piston-and-cylinder assembly (310), which is arranged between a horizontal supporting beam (309) associated with the frame system of the shoe press and the press shoe (300) and in which hydraulic fluid is supplied to a working chamber (325), hydraulic fluid
15 being also supplied to a compartment (301), which is arranged on the outside of the piston-and-cylinder assembly (310) in such a manner that the hydraulic fluid therein exerts directly or individually upon the press shoe (300) a force which is opposed to the force exerted
20 upon the press shoe (300) by the hydraulic fluid in said working chamber (325), characterized in that the working chamber (325) is supplied with hydraulic fluid via ducts (326, 327) arranged in the piston (330), while the compartment (301) is supplied with hydraulic
25 fluid via a duct (302) formed in the press shoe.

10. A shoe press as claimed in claim 9, characterized in that the duct (302) in the press shoe is supplied with hydraulic fluid via a pipe (303) which is releasably attached to the press shoe and the
30 bore (306) of which communicates with the duct (302) via a hole (308) formed in the pipe wall.



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01758

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: D21F 3/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: D21F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 19515832 C1 (VOITH SULZER PAPIERMASCHINEN GMBH), 2 May 1996 (02.05.96) -- -----	1,4,9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 January 1999

Date of mailing of the international search report

26-01-1999

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Olov Jensen
 Telephone No. +46 8 782 25 00

01/12/98

PCT/SE 98/01758

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19515832 C1	02/05/96	CA 2173890 A	30/10/96
		DE 19607211 A	28/08/97
		EP 0740016 A	30/10/96
		FI 960908 A	30/10/96
		JP 8302582 A	19/11/96
		US 5688375 A	18/11/97
